

Stair Riser Luminaire

91.1 CG-S



91.1 CG-S
with black grid



91.1 CG-S
with legend foil PL

Technical data







91.1 CG-S

Luminous flux Φ_E/Φ_N at the end of rated operating time	75 %
Enclosure material	Aluminium, die casting
Weight	0.76 kg
Enclosure colour	white/black
Type of mounting	Recessed into stairs
Dimensions (mm) (L x H x D)	235 x 100 x 82
Connection terminals	Loop terminals 3 x 2.5 mm ²
Voltage ranges	230 V 50/60 Hz, 220 V DC +25/-20 %
Current consumption (220 V battery)	20 mA
Power consumption	10 VA
Permissible temperature range	-10°C to +40°C
Lamp	4 W/T16
Insulation class	I
Degree of protection	IP 54

Ordering details

Type	Scope of supply	Order No.
91.1 CG-S	Complete with CEWA GUARD monitoring and 20 digit address switch, with opaque cover	4 0071 341 920
91.1 CG-S	Complete with CEWA GUARD monitoring and 20 digit address switch, with black grid	4 0071 340 621

Accessories

Type	Order No.
Concrete mounting box	4 0071 079 752
Recessed wall mounting box (cavity wall mounting set)	4 0033 079 456
Cover PL acc. DIN 4844 	4 0071 349 642
Cover PR acc. DIN 4844 	4 0071 349 643
Cover PU acc. DIN 4844 	4 0071 349 644
Cover PL 	4 0071 345 011
Cover PR 	4 0071 345 012
Cover PU 	4 0071 345 013

Dimensions (mm)

