

Explosion Protected Escape Sign Luminaire EXIT CG-S






EXIT CG-S

Technical data

EXIT CG-S

Marking to 94/9/EG	⊕ II 2 G / ⊕ II 2 D T60 °C
Type of protection	EEx em ib IIC T6 (ta max. +40 °C), T5 (ta max. +50 °C)
EC-Type Examination Certificate	PTB 02 ATEX 2111
Viewing distance	25 m (gem. DIN EN 1838)
Enclosure material	Polycarbonate
Enclosure colour	Grau, RAL 7035
Protective cover	Polycarbonate
Rated voltage EXIT CG-S	AC: 220 - 230 V ± 10 %, 50/60 Hz DC: 220 V + 25 % - 20 %
Power consumption	approx. 6 VA
Degree of protection acc. to EN 60529	IP 65
Insulation class	I
Permissible temperature range	- 20 °C to + 50 °C
Cable entries	1 x Ex e-cable entry M20 x 1,5 (plastic) 1 x Ex e-blanking plug M20 x 1,5
Connecting terminals	3 x 2.5 mm ² double terminals
Dimensions in mm (L x H x D)	340 x 150 x 75
Mounting	Wall mounting
Lamps	High-efficiency LEDs, white

Ordering details

Type	Scope of delivery	Order No.
EXIT CG-S	incl. cover with silk-screen legend PR 	1 2191 020 001
	incl. cover with silk-screen legend PL 	1 2191 020 002
	incl. cover with silk-screen legend PU 	1 2191 020 003

Other silk-screen legends on demand

Dimensions in mm

