

Dust-Explosion Protected Escape Sign Luminaire D22-Ex 6011.1 CG-S/ D22-Ex 6011.1

Technical data

D22-Ex 6011.1/D22-Ex 6011.1 CG-S

Marking to 94/9/EG	⊕ II 3 D Ex tD A22 IP 55 T80 °C
EC-Type Examination Certificate	BVS 07 ATEX E 129X
Viewing distance	approx. 26 m
Enclosure material	Polycarbonate, light grey
Enclosure colour	Grey RAL 7035
Protective cover	Polycarbonate
Rated voltage	AC: 230 V ± 10 %, 50-60 Hz DC: 220 V + 25 % - 20 %
Power consumption	approx. 16 VA
Battery current	approx. 30 mA
Protection category EN 60529	IP 55
Insulation class	I
Permissible temperature range	-10 °C to +40 °C
Cable entries	1 x EEx e-cable entry M20 x 1.5 1 x EEx e-blanking plug M20 x 1.5 5
Connecting terminals	3 x 2.5 mm ² double terminals
Dimensions in mm (L x H x D)	400 x 160 x 103
Mounting	Wall- and ceiling mounting
Lamps	8 W fluorescent lamp T5
Weight	approx. 1.4 kg



D22-Ex 6011.1



D22-Ex 6011.1 CG-S

Ordering details

Type	Scope of supply	Order No.
D22-Ex 6011.1 CG-S acc. DIN 4844	Luminaire with CEWA GUARD monitoring and 20 digit address switch, with cover incl. 3 legends PL, PR, PU	D22 4 0071 349 523
D22-Ex 6011.1 acc. DIN 4844	Luminaire with cover incl. 3 legends PL, PR, PU	D22 4 0071 349 520
D22-Ex 6011.1 CG-S	Luminaire with CEWA GUARD monitoring and 20 digit address switch, with cover incl. 3 legends PL, PR, PU	D22 4 0071 352 710
D22-Ex 6011.1	Luminaire with cover incl. 3 legends PL, PR, PU	D22 4 0071 352 711

Dimensions in mm

