

# Edge Luminaires with Legend Brilliant LED 1503 LED CG-S to 1803 LED CG-S



1503 LED CG-S  
Design white



1603 LED CG-S  
Design white



1703 LED CG-S  
Design white



1803 LED CG-S  
with metal bezel white

## Technical data


### 1503 LED CG-S to 1803 LED CG-S

<b>Viewing distance with pictogram</b>	<b>20 m</b>
Luminous flux DC-operation	100 % 66 lm 65 % 47 lm
Enclosure material	Aluminium
Enclosure colour	White
Weight incl. panel	1503 LED CG-S / 2.3 kg 1603 LED CG-S / 2.2 kg 1703 LED CG-S / 1.8 kg 1803 LED CG-S / 2.9 kg
Dimensions in mm (L x H x D)	see dimensional drawings
Connection terminals	3 x 2.5 mm <sup>2</sup>
Voltage ranges	230 V 50/60 Hz, 220 V DC + 25/- 20 %
Current consumption (220 V battery)	100 % 23 mA 65 % 17 mA
Power consumption	100 % 8,4 VA 65 % 6,1 VA
Permissible temperature range	-10°C to + 40°C
Lamp	3 x 1 W LED
Insulation class	I
Degree of protection	IP 20

## Ordering details

Type	Scope of supply	Order No.
1503 LED CG-S	Edge luminaire with CEWA GUARD monitoring and 20 digit address switches; with wall bracket for parallel to wall mounting, without panel; design: white, RAL 9010	4 0071 350 900
1603 LED CG-S	Edge luminaire with CEWA GUARD monitoring and 20 digit address switches; with wall bracket, without panel; design: white, RAL 9010	4 0071 350 901
1703 LED CG-S	Edge luminaire with CEWA GUARD monitoring and 20 digit address switches; for ceiling mounting, with accessories for chain suspension or for pendulum mounting, without panel; design: white, RAL 9010	4 0071 350 902
1803 LED CG-S	Edge luminaire CEWA GUARD monitoring and 20 digit address switches; for ceiling mounting, without panel and without bezel	4 0071 350 638
Bezels for 1803	Metal bezel white, RAL 9010	4 0071 348 860

# Edge Luminaires with Legend Brillant LED 1503 LED CG-S to 1803 LED CG-S



Panel PR/PL

## Ordering details for panels

Type	Scope of supply	Order No.
Panel PL/PR acc. DIN 4844	Double-sided silk screened legend	4 0071 350 943
Panel PU/PU acc. DIN 4844	Double-sided silk screened legend	4 0071 350 944
Panel PU/BL acc. DIN 4844	Double-sided silk screened legend	4 0071 350 945
Panel PL/PR	Double-sided silk screened legend	4 0071 350 940
Panel PU/PU	Double-sided silk screened legend	4 0071 350 941
Panel PU/BL	Double-sided silk screened legend	4 0071 350 942

## Accessories

Type	Scope of supply	Order No.
Concrete ceiling box for 1803 ...	for installation in concrete ceilings	4 0071 348 725
Mounting set for 1803 ...	for installation in concrete ceiling box	4 0071 341 720
Pendulum set, white	0.5 m with wall bracket for 1703, RAL 9010	4 0071 348 721
Pendulum set, white	1.5 m with wall bracket for 1703, RAL 9010	4 0071 348 722
Chain suspension metal	chain suspension for 1703	4 0071 348 723

Dimensions in mm

