



Self contained luminaire Style Variant 28011 LED CGLine



28011 LED CGLine
with cover PL
acc. DIN 4844

Dimensions in mm









Technical data

28011 LED CGLine

Viewing distance	32 m
Luminous flux $\Phi_E / \Phi_{E, Nenn}$ at the end of rated operating time	1h – 50 % / 3h – 20 %
Material enclosure	Polycarbonate (grey), RAL 7035
Type of mounting	Wall mounting
Dimensions (mm) (L x H x D)	342 x 200 x 68
Weight	1.2 kg
Battery	rechargeable, maintenance free, gas tight
Duration of emergency lighting 1 h and 3 h	NiMH 4.8 V / 1.1 Ah
Connection terminals	mains connection 3 x 2.5 mm ² / bus connection 2 x 1.5 mm ²
Rated voltage	230 V 50 Hz
Power consumption	12.8 VA
Lamp	4 x 1W LED
Insulation class	II
Degree of protection	IP 41
Permissible temperature range	Maintained mode –5 °C to +30 °C Non-maintained mode 0 °C to +35 °C

Ordering details

Type	Duration of emergency lighting (h) battery	Scope of delivery	Order No.
28011 1-3/D LED CGLine	1h / 3h	Luminaire enclosure with automatic test function, without cover	4 0071 352 221
Cover PL acc. DIN 4844		Cover with silk-screened legend 	4 0071 349 320
Cover PR acc. DIN 4844		Cover with silk-screened legend 	4 0071 349 321
Cover PU acc. DIN 4844		Cover with silk-screened legend 	4 0071 349 323
Cover PL		Cover with silk-screened legend 	4 0071 348 011
Cover PR		Cover with silk-screened legend 	4 0071 348 012
Cover PU		Cover with silk-screened legend 	4 0071 348 013

Accessories


Type	Scope of supply	Order No.
Wire guard AP		4 0071 348 370

Self contained luminaire Style Variant 28021 LED CGLine




28021 LED CGLine
with cover PU
acc. DIN 4844


Dimensions in mm




28021 LED CGLine



28021 LED CGLine with ceiling fastening



28021 LED CGLine with wall bracket



Ordering details

28021 LED CGLine

Viewing distance	32 m
Luminous flux Φ_E/Φ_{Nenn} at the end of rated operating time	1h – 50 % / 3h – 20 %
Material enclosure	Polycarbonate (grey), RAL 7035
Type of mounting	Ceiling, pendulum, chain or wall bracket mounting
Dimensions (mm) (L x H x D)	342 x 202 x 92
Weight	1.3 kg
Battery	rechargeable, maintenance free, gas tight NiMH 7.2 V / 1.1 Ah
Duration of emergency lighting	mains connection 3 x 2.5 mm ² bus connection 2 x 1.5 mm ²
Rated voltage	230 V 50 Hz
Power consumption	22.6 VA
Lamp	8 x 1W LED
Insulation class	II
Degree of protection	IP 41
Permissible temperature range	Maintained mode –5 °C to +30 °C Non-maintained mode 0 °C to +35 °C

Ordering details

Type	Duration of emergency lighting (h) battery	Scope of supply	Order No.
28021 1-3/D LED CGLine*	1h / 3h	Luminaire enclosure with automatic test function, without covers	4 0071 352 223
Cover PL acc. DIN 4844		Cover with silk-screened legend	4 0071 349 320
Cover PR acc. DIN 4844		Cover with silk-screened legend	4 0071 349 321
Cover PU acc. DIN 4844		Cover with silk-screened legend	4 0071 349 323
Cover PL		Cover with silk-screened legend	4 0071 348 011
Cover PR		Cover with silk-screened legend	4 0071 348 012
Cover PU		Cover with silk-screened legend	4 0071 348 013

* Each luminaire requires 2 covers.

Accessories

Type	Scope of delivery	Order No.
Ceiling/chain fastening		4 0071 350 432
Pendulum set 0.5 m	with canopy	4 0071 350 400
Wall bracket		4 0071 350 418