

Portable Emergency Lights W 270.3/4, W 270.3/7 and Charging Unit Z 345.3 with Emergency Lighting Function



W 270.3/4
Separate charging unit

Technical data

W 270.3/4, W 270.3/7 with emergency lighting function for separate charging unit

Slip-on filters (incl.)	red, orange, white
Enclosure material	impact resistant, non-adhesive plastic
Enclosure colour	grey
Duration of emergency lighting Battery 4 Ah (7 Ah)	3.5 h (6.5 h) with incandescent lamp 5 V/5 W (main) 12.0 h (25 h) with incandescent lamp 4.8 V/1.5 W (pilot)
Battery	rechargeable, maintenance free, gas tight NC-Akku 4.8 V / 4 Ah NC-Akku 4.8 V / 7 Ah
Lamp	Main beam 5 V / 5 W Pilot beam 4.8 V / 1.5 W
Insulation class	II
Degree of protection	IP 54
Switch function	Flashlight, maintained light and pilot light

Ordering details

Type	Battery	Order No.
W 270.3/4	4 Ah	1 1145 000 270
W 270.3/7	7 Ah	1 1145 000 272

Accessories

Accessories/spare part	Order No.
Incandescent lamp -5 V / 5 W (5 pcs.) -4.8 V / 1.4 W (10 pcs.)	4 0071 345 265 4 0071 345 264
Rechargeable NiCd-accu. 4,8 V/4 Ah	4 0071 345 248
Rechargeable NiCd-accu. 4,8 V/7 Ah	4 0071 345 253
Slip-on filter set red, orange and radial difuser cap	2 1145 995 000

Lighting engineering

see page 7/28

Technical Data

Z 345.3 for portable emergency lights W 270.3

Enclosure material	impact resistant, non-adhesive plastic
Enclosure colour	grey
Rated voltage	230 V 50/60 Hz
Rated load	10 VA
Insulation class	II
Degree of protection	IP 44

Ordering details

Type	Order No.
Charging unit Z 345.3	4 0071 341 145



Charging unit Z 345.3
for portable emergency lights
W 270.3/4 and W 270.3/7