

10 & 15 JOULE XENON BEACONS EExd(e), Weatherproof XB10 Range



Introduction

These compact and lightweight 10 & 15 Joule beacons have been designed for use in potentially explosive atmospheres and harsh environmental conditions. The beacon housing, including the flamepaths, is manufactured completely from a UV stable glass reinforced polyester which is ideally suited for use offshore and onshore.

Stainless Steel screws and mounting bracket are incorporated ensuring a totally corrosion free unit. An additional body clamp is available for high-vibration environments.

Units can be painted to customer specification and supplied with identification labels.

- ★ Zone 1 and Zone 2 use.
- ★ EExd(e) IIB T4.
- ★ ATEX Approved, Ex II 2G.
- ★ BASEEFA Certified.
- ★ GOST 'R' Certified.
- ★ Brazilian (Inmetro) Certified.
- ★ IP66 and IP67.
- ★ Certified Temperature* -55°C to +55°C.
- ★ Low current 10 Joule version available.
- ★ Corrosion Free GRP.
- ★ Various lens colours.
- ★ Lens guard fitted as standard.
- ★ Stainless steel mounting bracket & screws.
- ★ Replaceable twin tubes.
- ★ Optional telephone initiate.
- ★ Optional earth continuity.

* Model dependent.

MEDC Ltd, Colliery Road,
Pinxton, Nottingham NG16 6JF, UK.
Tel: +44 (0)1773 864100
Fax: +44 (0)1773 582800

MEDC International, 5829 West Sam Houston Parkway,
North, Suite 1005, Houston, Texas 77041, USA.
Tel: +1 (713) 937 9772
Fax: +1 (713) 937 9773

MEDC Norway, Auglaendsmyraa 6,
4016, Stavanger, Norge.
Tel: +47 913 92 289
Fax: +47 914 46 030

Sales Enq. Fax: +44 (0)1773 582830 Sales Orders Fax: +44 (0)1773 582832
E-Mail: sales@medc.com Web: www.medc.com

MEDC

Specification

Certification: CENELEC EN50014, EN50018, EN50019.
Cert. No. BAS00ATEX2226X EExde IIB T4.
Cert. No. BAS00ATEX2204X EExd IIB T4.
Zone 1 and Zone 2.
GOST 'R' Certification – 1Exd IIB T4 / 2Exde IIB T4, Russian
Fire Alarm Approved (VNIPO)
Brazilian (Inmetro) Certified: BR-Ex d IIB T4
BR-Ex de IIB T4

Materials: Body & Cover - Glass Reinforced Polyester (GRP).
Lens - Glass.
Screws & Bracket - Stainless Steel 316

Finish: Natural or painted to customer requirements.

Voltage	DC				AC			
	24	48	110	220/240/254	24	48	110	220/240/254
Tube Energy (J)	10	15	10	15	10	15	10	15
Peak Current Consumption (mA)	700	1200	300	560	190	300	100	145
Effective Intensity (Cd)	285	330	285	330	285	330	285	330
Peak Intensity (Cd)	74179	111269	74179	111269	74179	111269	74179	111269
Power Consumption (W)	16.8	28.8	14.4	26.8	20.9	33	24	34.8
Flash Rate	1Hz (other flash rates available on request, please specify)							

Note: The above figures (Cd) are for a clear lens @ 1Hz flash rate.

For Coloured Lenses:

Colour	Red	Blue	Amber	Green	Yellow
Multiplying Factors (Approximate)	0.15	0.12	0.51	0.49	0.86

Weight: EExd 2.8kg. EExde 3.6kg.

Certified Temperature: 15J unit: EExd -55°C to +40°C.
EExde -50°C to +40°C.
10J unit: EExd -55°C to +55°C.
EExde -50°C to +45°C.


Ingress Protection: IP66 & IP67.

Fire Retardancy: GRP is fire retardant to ISO 1210.

Terminals: 4 x 2.5mm² (d.c.), 6 x 2.5mm² (a.c.).

Mounting: Wall mounted via bracket.

Entries: Up to 2 x M20 (EExd). Up to 3 x M20 (EExde).
Optional: 1 x 3m cable tail (both EExd & EExde).



Ordering Requirements

The following code is designed to help in the selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box. **Standard products available ex-stock as follows:**

PRODUCT	DESCRIPTION
XB10D024FRNN2BN	ATEX approved Ex II 2G, certified EExdIIB T4, 15 Joule Xenon, 24V d.c., 60 flashes/min., red lens, lens guard, 2 x M20 entries, natural black finish.
XB10D024FANN2BN	ATEX approved Ex II 2G, certified EExdIIB T4, 15 Joule Xenon, 24V d.c., 60 flashes/min., amber lens, lens guard, 2 x M20 entries, natural black finish.
XB10D240FRNN2BN	ATEX approved Ex II 2G, certified EExdIIB T4, 15 Joule Xenon, 240V a.c., 60 flashes/min., red lens, lens guard, 2 x M20 entries, natural black finish.
XB10D240FANN2BN	ATEX approved Ex II 2G, certified EExdIIB T4, 15 Joule Xenon, 240V a.c., 60 flashes/min., amber lens, lens guard, 2 x M20 entries, natural black finish.

Model	Certification	Voltage	Power	Lens Colour	Labels	Options	Entries	Body Colour
XB10								

<table border="1"> <tr> <th>Certification</th> <th>Code</th> </tr> <tr> <td>Uncertified</td> <td>W</td> </tr> <tr> <td>EExd</td> <td>D</td> </tr> <tr> <td>EExde</td> <td>E</td> </tr> <tr> <td>GOST 'R' Exd</td> <td>DG*</td> </tr> <tr> <td>GOST 'R' Exe</td> <td>EG*</td> </tr> <tr> <td>Inmetro EExd</td> <td>DM</td> </tr> <tr> <td>Inmetro EExde</td> <td>EM</td> </tr> </table>	Certification	Code	Uncertified	W	EExd	D	EExde	E	GOST 'R' Exd	DG*	GOST 'R' Exe	EG*	Inmetro EExd	DM	Inmetro EExde	EM	<table border="1"> <tr> <th>Voltage</th> <th>Code</th> </tr> <tr> <td>24V d.c.</td> <td>024</td> </tr> <tr> <td>48V d.c.</td> <td>048</td> </tr> <tr> <td>110V a.c.</td> <td>110</td> </tr> <tr> <td>220V a.c.</td> <td>220</td> </tr> <tr> <td>240V a.c.</td> <td>240</td> </tr> <tr> <td>254V a.c.</td> <td>254</td> </tr> </table>	Voltage	Code	24V d.c.	024	48V d.c.	048	110V a.c.	110	220V a.c.	220	240V a.c.	240	254V a.c.	254	<table border="1"> <tr> <th>Colour</th> <th>Code</th> </tr> <tr> <td>Red</td> <td>R</td> </tr> <tr> <td>Blue</td> <td>B</td> </tr> <tr> <td>Green</td> <td>G</td> </tr> <tr> <td>Yellow</td> <td>Y</td> </tr> <tr> <td>Amber</td> <td>A</td> </tr> <tr> <td>Clear</td> <td>C</td> </tr> </table>	Colour	Code	Red	R	Blue	B	Green	G	Yellow	Y	Amber	A	Clear	C	<table border="1"> <tr> <th>Tag/Duty Label</th> <th>Code</th> </tr> <tr> <td>None</td> <td>N</td> </tr> <tr> <td>*Yes</td> <td>Y</td> </tr> <tr> <td colspan="2">*(Please specify)</td> </tr> </table>	Tag/Duty Label	Code	None	N	*Yes	Y	*(Please specify)		<table border="1"> <tr> <th>Entries</th> <th>Code</th> </tr> <tr> <td>EExd</td> <td></td> </tr> <tr> <td>1 x M20</td> <td>1B</td> </tr> <tr> <td>1 x PG13.5</td> <td>1P</td> </tr> <tr> <td>2 x M20</td> <td>2B</td> </tr> <tr> <td>2 x PG13.5</td> <td>2P</td> </tr> <tr> <td>EExd(e)</td> <td></td> </tr> <tr> <td>3 x M20</td> <td>3B</td> </tr> </table>	Entries	Code	EExd		1 x M20	1B	1 x PG13.5	1P	2 x M20	2B	2 x PG13.5	2P	EExd(e)		3 x M20	3B	<table border="1"> <tr> <th>Finish</th> <th>Code</th> </tr> <tr> <td>Natural Black</td> <td>N</td> </tr> <tr> <td>Red</td> <td>R</td> </tr> <tr> <td>Blue</td> <td>B</td> </tr> <tr> <td>Yellow</td> <td>Y</td> </tr> <tr> <td>Grey</td> <td>G</td> </tr> <tr> <td>White</td> <td>W</td> </tr> <tr> <td>Special Finish</td> <td>S</td> </tr> </table>	Finish	Code	Natural Black	N	Red	R	Blue	B	Yellow	Y	Grey	G	White	W	Special Finish	S
Certification	Code																																																																																								
Uncertified	W																																																																																								
EExd	D																																																																																								
EExde	E																																																																																								
GOST 'R' Exd	DG*																																																																																								
GOST 'R' Exe	EG*																																																																																								
Inmetro EExd	DM																																																																																								
Inmetro EExde	EM																																																																																								
Voltage	Code																																																																																								
24V d.c.	024																																																																																								
48V d.c.	048																																																																																								
110V a.c.	110																																																																																								
220V a.c.	220																																																																																								
240V a.c.	240																																																																																								
254V a.c.	254																																																																																								
Colour	Code																																																																																								
Red	R																																																																																								
Blue	B																																																																																								
Green	G																																																																																								
Yellow	Y																																																																																								
Amber	A																																																																																								
Clear	C																																																																																								
Tag/Duty Label	Code																																																																																								
None	N																																																																																								
*Yes	Y																																																																																								
*(Please specify)																																																																																									
Entries	Code																																																																																								
EExd																																																																																									
1 x M20	1B																																																																																								
1 x PG13.5	1P																																																																																								
2 x M20	2B																																																																																								
2 x PG13.5	2P																																																																																								
EExd(e)																																																																																									
3 x M20	3B																																																																																								
Finish	Code																																																																																								
Natural Black	N																																																																																								
Red	R																																																																																								
Blue	B																																																																																								
Yellow	Y																																																																																								
Grey	G																																																																																								
White	W																																																																																								
Special Finish	S																																																																																								

<table border="1"> <tr> <th>Power</th> <th>Code</th> </tr> <tr> <td>10J</td> <td>T</td> </tr> <tr> <td>15J</td> <td>F</td> </tr> </table>	Power	Code	10J	T	15J	F	<table border="1"> <tr> <th>Option</th> <th>Code</th> </tr> <tr> <td>Telephone Initiate</td> <td>T</td> </tr> <tr> <td>Earth Continuity</td> <td>E</td> </tr> <tr> <td>3m cable tail</td> <td>G</td> </tr> <tr> <td>None</td> <td>N</td> </tr> </table>	Option	Code	Telephone Initiate	T	Earth Continuity	E	3m cable tail	G	None	N
Power	Code																
10J	T																
15J	F																
Option	Code																
Telephone Initiate	T																
Earth Continuity	E																
3m cable tail	G																
None	N																

*VNIPO Approved as standard.



All the above specifications, dimensions, weights and tolerances are nominal (typical) and MEDC reserve the right to vary all data without prior notice. No liability is accepted for any consequence of use.