

# STEADY BEACONS

## EExd, Weatherproof

### FL11, FB11, FL12 & FB12 Range



FL11/FB11 Range



FL12/FB12 Range

## Introduction

These certified steady beacons have been designed for use in potentially explosive atmospheres and harsh environmental conditions. The enclosures are suitable for use offshore or onshore, where light weight combined with corrosion resistance is required.

The beacon housing is manufactured completely from a U.V. stable, glass reinforced polyester. Stainless steel screws and mounting bracket are available ensuring a totally corrosion free product.

Units can be painted to customer specification and supplied with identification labels.

- ★ Zone 1 and Zone 2 use.
- ★ EExd, IIB T4/T5.
- ★ ATEX approved, Ex II 2GD\*.
- ★ UL listed for USA and Canada\*
  - Class I, Div. 2, Groups C & D.
  - Class I, Zone 1, AExd IIB T4/T5.
- ★ BASEEFA Certified.
- ★ GOST 'R' Certified.
- ★ Brazilian (Inmetro) Certified.
- ★ Fluorescent.
- ★ Filament.
- ★ IP66 and IP67.
- ★ Certified temperature  $-55^{\circ}\text{C}$  to  $+55^{\circ}\text{C}$ .\*
- ★ Corrosion resistant GRP.
- ★ Optional stainless steel backstrap.
- ★ Various lens colours.
- ★ Optional lens guard.
- ★ 2 x M20 or 2 x  $1\frac{1}{2}$ " NPT cable entries.
- ★ Earth continuity option.

\*Model dependent



MEDC Ltd, Colliery Road,  
Pinxton, Nottingham NG16 6JF, UK.  
Tel: +44 (0)1773 864100  
Fax: +44 (0)1773 582800

MEDC International, 5829 West Sam Houston Parkway,  
North, Suite 1005, Houston, Texas 77041, USA.  
Tel: +1 (713) 937 9772  
Fax: +1 (713) 937 9773

MEDC Norway, Auglaendsmyrå 6,  
4016, Stavanger, Norge.  
Tel: +47 913 92 289  
Fax: +47 914 46 030

Sales Enq. Fax: +44 (0)1773 582830 Sales Orders Fax: +44 (0)1773 582832  
E-Mail: [sales@medc.com](mailto:sales@medc.com) Web: [www.medc.com](http://www.medc.com)





## Specification

**Models:** FL11 & FL12 – Fluorescent, EExd.  
FB11 & FB12 – Filament, EExd.  
FB12 – Filament, EExd & UL Listed.

**Certification:** CENELEC EN50014 and EN50018.  
FB11/FL11 Cert. No. BAS99 ATEX 2195X.  
FB12/FL12 Cert. No. BAS99 ATEX 2196.  
BASEEFA EExd IIB – for T rating see table.  
**UL Listed for USA and Canada** (FB11 & FB12 only)  
– Class I, Div. 2, Groups C & D and  
– Class I, Zone 1, AExd IIB T4/T5. UL Listing No. E187814.  
**GOST 'R':** IExd IIB (for T ratings see table).  
**Brazilian (Inmetro) Certified:** BR-Ex d IIB T4/T5/T6

**Voltage:** FL11 & FL12 – 24V d.c., 240V a.c.  
FB11 & FB12 – 24V d.c., 48V d.c.  
– 110V a.c., 120V a.c., 220V a.c., 240V a.c., 254V a.c.

**Fluorescent:** 5 Watt type light output 250 Lumens (FL11 24V d.c. version only) – G23 lamp holder.  
10 Watt type light output 600 Lumens (FL11 240V a.c. version only) – G23 lamp holder.  
13 Watt type light output 900 Lumens (FL12, per tube) – G24Q-1 lamp holder.

**Filament:** FB11 – 10W filament fitted as standard – (SBC lamp holder).  
FB12 – 60W or 100W single filament fitted as standard. Others may be available (UL Listed – 60W only) – (ES27 lamp holder).

**Material:** Body: – Glass reinforced polyester (GRP).  
Lens: – Glass.  
Cover Screws + Backstrap: – Stainless steel 316.

**Finish:** Natural black or painted to customer specification.

**Ingress Protection:** IP66 & IP67.

**Fire Retardancy:** GRP is fire retardant to ISO 1210.

**Earth Continuity:** Optional for metal glands provided via a brass plate.

**Terminals:** FL11 (a.c.) 4 x 2.5mm<sup>2</sup>.  
FL11 (d.c.), FB11 6 x 2.5mm<sup>2</sup>.  
FB12/FL12 6 x 6.0mm<sup>2</sup>.  
FB12 UL 6 x 10 AWG.

**Labels:** Duty/Tag Label optional.

**Entries:** 2 x 20mm ISO EExd.  
2 x 1/2" NPT UL Listed.

**Certified:** FB11 & FB12, EExd = -55°C to + 55°C\*.

**Temperature:** FL11 & FL12, EExd = -20°C to + 55°C\*.  
\*Model dependent – see table for details.

Certified Temperature Ratings				
Type	Voltage/Wattage	T Class	Min. Amb.	Max. Amb.
FB11	All	T5	-55°C	+40°C
		T4	-55°C	+55°C
FL11	All	T5	-20°C	+40°C
		T4	-20°C	+55°C
FB12	60W	T5	-55°C	+40°C
	60W	T4	-55°C	+55°C
	100W	T3	-55°C	+30°C
FL12	13W a.c. & d.c.	T6	-20°C	+40°C
	13W a.c.	T5	-20°C	+55°C
	26W a.c.	T5	-20°C	+40°C
	26W a.c.	T4	-20°C	+55°C
	39W a.c.	T4	-20°C	+40°C

**Weight:** FL11, FB11 – 2.8 kg\*.  
FL12 – 7.2 kg\*.  
FB12 – 7.6 kg\*.  
\*dependant on model.

## Ordering Requirements

The following code is designed to help in the selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box.

Unit Type	Certification	Voltage	Lamp Wattage	Lens Colour	Lens Guard	Unit Fixing	Earth Continuity	Tag/Duty Label	Finish
<b>FL11</b> <b>FB11</b> <b>FL12</b> <b>FB12</b>	Cert. Code Uncertified W ATEX B UL Listed* UL GOST 'R' G Inmetro DM				Guard Code None N Yes Y	Unit Fixing Code Direct Mounting D Backstrap B		Label Code None N Yes Y (Please specify)	Finish Code Natural Black N Red R Blue B Yellow Y Grey G White W Special Finish S
*UL listed only available FB11 & FB12.									
Voltage Code 24V d.c. 024 48V d.c.* 048 110V a.c.* 110 120V a.c.† 120 220V a.c.* 220 240V a.c. 240 254V a.c.* 254 Other voltages available, please specify. *FB11 & FB12 only †FB12 UL Listed only	Lamp Wattage Code FL11† 5W d.c. (1 x 5W tube)* 5 10W a.c. (1 x 10W tube)* 10 FB11† 10W a.c. & d.c. (1 x 10W bulb) 10 FL12 13W a.c. & d.c. (1 x 13W tube)* 13 26W a.c. (2 x 13W tubes)* 26 39W a.c. (3 x 13W tubes)* 39 FB12 60W a.c. & d.c. (1 x 60W bulb) 60 100W a.c. & d.c. (1 x 100W bulb) 100								
*Not available in UL versions. †Inmetro Only available on FL11 & FB11									



All the above specifications, dimensions, weights and tolerances are nominal (typical) and MEDC reserve the right to vary all data without prior notice. No liability is accepted for any consequence of use.