



ISO9001 Certified

MEDC Ltd
Colliery Road,
Pinxton,
Nottingham,
NG16 6JF
United Kingdom

Tel: +44 (0) 1773 864100
Fax: +44 (0) 1773 582800
E-mail: sales@medc.com
Web-site: www.medc.com


MEDC International
Houston USA

MEDC Norway
Stavange Norway

Phone: +1 (713) 937 9772 Fax: +1 (713) 937 9773 E-Mail: us.sales@medcint.com

Phone: +47 51 82 98 98 Fax: +47 51 82 98 91 E-Mail: norway.sales@medc.com

DB19 – 15W Range



Certification: Weatherproof, ATEX Compliant for zones 2 gas and dust, EEx n II T4, ATEX II 3 GD

Material/Colour	Aluminium body painted white
Mounting	Bracket
Termination	4 x 2.5mm ²
Weight	2.4kg (5.2lb)
IP-Rating	54
Max. / Min. amb. temp	-55°C to +55°C (-67°F to +131°F)
Rated / Max. power	15 Watts
SPL 1W/1m	92 dba
SPL rated power	104 dba
Effective freq. range	120 – 20000Hz
Dispersion 1kHz	130
Options	Body colour, Transformer Voltage

Transformer Tappings	Power
	15W
1:2	15.0
2:3	7.5
3:4	5.0
1:3	4.0
2:4	2.0
1:4	0.8

