



ISO9001 Certified

MEDC Ltd
Colliery Road,
Pinxton,
Nottingham,
NG16 6JF
United Kingdom

Tel: +44 (0) 1773 864100
Fax: +44 (0) 1773 582800
E-mail: sales@medc.com
Web-site: www.medc.com


MEDC International
Houston USA

MEDC Norway
Stavange Norway

Phone: +1 (713) 937 9772 Fax: +1 (713) 937 9773 E-Mail: us.sales@medcint.com

Phone: +47 51 82 98 98 Fax: +47 51 82 98 91 E-Mail: norway.sales@medc.com

DB14 – 15W Range




Certification:

Weatherproof and BS5839 part 8 compliant available only.

Material/Colour	Glass reinforced Polyester / Natural Grey
Mounting	Bracket
Termination	8 x 2.5mm ²
Weight	2.6kg (5.7lb)
IP-Rating	66 & 67
Max. / Min. amb. temp	-55°C to +70°C (-67°F to +158°F)
Rated / Max. power	15 Watts
SPL 1W/1m	107dba
SPL rated power	117 dba
Effective freq. range	400 – 7000Hz
Dispersion 1kHz	140
Options	Body colour, Transformer Voltage, Duty / Tag label.

Transformer Tappings	Power
	15W
1:2	15.0
2:3	7.5
3:4	5.0
1:3	4.0
2:4	2.0
1:4	0.8

Frequency Response @ 1W/1m for 15W unit
(1/3 Octave Pink Noise)



Polar Plot at 1KHz

