

COMBINATION – BEACON SOUNDER

EEExde, Weatherproof

CU1 Range



Introduction

This range of beacon/sounder units, intended for use in potentially explosive gas and dust atmospheres, has a power rating of up to 10 watts (sounder) and 10 joules (beacon) and is suitable for use in the harsh environmental conditions found offshore and onshore in the oil, gas and petrochemical industries.

The flamepaths, flare and body are manufactured from a UV stable glass reinforced polyester. Stainless steel screws and mounting stirrup are incorporated to ensure a corrosion-free product. A tapered flamepath is used to overcome the problems of assembly of parallel spigot flamepaths.

- ★ Zone 1, Zone 2 & non-Ex use.
 - ★ EExde IIB T3.
 - ★ ATEX approved, Ex II 2 G.
 - ★ CENELEC approved.
 - ★ GOST 'R' & 'K' Certified.
 - ★ BASEEFA certified.
 - ★ Brazilian (Inmetro) certified.
 - ★ IP66 and 67.
 - ★ Certified temperature -50°C to $+70^{\circ}\text{C}^*$.
 - ★ Up to 116 dB(A)*.
 - ★ Version with independent beacon/sounder operation now available.
 - ★ 27 Tones, user selectable (dual tone option)
 - ★ Tones comply with UK00A/PFEER guidelines
 - ★ Integral volume control
 - ★ GRP corrosion-free flamepath.
 - ★ Ratcheted swivel mounting stirrup.
 - ★ Stainless steel fixtures.
 - ★ Tapered flamepath.
- *Model dependent.

MEDC Ltd, Colliery Road,
Pinxton, Nottingham NG16 6JF, UK.
Tel: +44 (0)1773 864100
Fax: +44 (0)1773 582800

MEDC International, 5829 West Sam Houston Parkway,
North, Suite 1005, Houston, Texas 77041, USA.
Tel: +1 (713) 937 9772
Fax: +1 (713) 937 9773

MEDC Norway, Auglaendsmyrå 6,
4016, Stavanger, Norge.
Tel: +47 913 92 289
Fax: +47 914 46 030

Sales Enq. Fax: +44 (0)1773 582830 Sales Orders Fax: +44 (0)1773 582832
E-Mail: sales@medc.com Web: www.medc.com

MEDC

