

5 JOULE XENON STROBES

Hazardous Location, Weatherproof

XB11 Range



Strobe/Horn
Combination Unit



Now UL listed to +158°F (+70°C)
Ambient Temperature

Introduction

These certified strobes have been designed for use in potentially explosive atmospheres and harsh environmental conditions. The glass reinforced polyester enclosures are suitable for use offshore or onshore, where light weight combined with corrosion resistance is required.

The strobe housing is manufactured completely from a U.V. stable, glass reinforced polyester. Stainless steel screws and mounting bracket are incorporated ensuring a totally corrosion free product.

Units can be painted to customer specification and supplied with identification labels.

European, Chinese and other worldwide approvals are available, refer to main section of catalog.

- ★ UL listed for USA and Canada
 - Hazardous locations:
 - Class I, Div. 2, Groups C & D.
 - Class I, Zones 1 & 2, AExd IIB T5.
 - Ordinary locations: Visual-Signal Device.
- ★ CSFM approved.
- ★ ATEX approved.
- ★ Xenon.
- ★ Output 22,000 Candela.
- ★ NEMA 4x and 6, IP66 & 67.
- ★ 24V d.c., 110 & 240V a.c.
- ★ Certified temperature –67°F to +158°F.
–55°C to +70°C.
- ★ 4 wire monitored connection.
- ★ Corrosion resistant GRP.
- ★ Optional stainless steel backstrap.
- ★ Various lens colors.
- ★ Optional lens guard.
- ★ Available as a status light.


MEDC Ltd, Colliery Road,
Pinxton, Nottingham NG16 6JF, UK.
Tel: +44 (0)1773 864100
Fax: +44 (0)1773 582800

MEDC International, 5829 West Sam Houston Parkway,
North, Suite 1005, Houston, Texas 77041, USA.
Tel: +1 (713) 937 9772
Fax: +1 (713) 937 9773

MEDC Norway, Auglaendsmyrå 6,
4016, Stavanger, Norge.
Tel: +47 913 92 289
Fax: +47 914 46 030

Sales Enq. Fax: +44 (0)1773 582830 Sales Orders Fax: +44 (0)1773 582832
E-Mail: sales@medc.com Web: www.medc.com

MEDC



Specification

Certification: UL Listed for USA and Canada

– Hazardous locations:

Class I, Div. 2, Groups C & D

Class I Zones 1 & 2, AExd IIB T5.

UL Listing No. E187894.

– Ordinary locations: Visual-Signal Device.

UL Listing No. S8128.

ATEX approved: EExd IIB T5/T6.

Cert. No. 99 ATEX 2195X.

CENELEC EN50014 and EN50018.

Material: Body: – Glass reinforced polyester.

Lens: – Glass

Cover Screws + Backstrap: – Stainless steel 316.

Finish: Natural black or painted to customer specification.

Weight: 5 1/2 lb/2.5kg.

Certified Temperature: –67°F to +158°F (–55°C to +70°C.) hazardous locations.

–67°F to +131°F (–55°C to +55°C) ordinary locations.

Ingress Protection: NEMA 4x and 6, IP66 & 67.

Terminals: 6 off suitable for up to 14 AWG conductor size.

Labels: Duty/Tag Label optional.

Entries: 2 x 1 1/2" NPT.

Strobe/Sounder Unit: The beacon may be combined with an MEDC sounder to create a visual/audible alarm. Contact MEDC for price and specification.

	DC	AC50/60 Hz	
Voltage	24	110	240
XB11 Tube Energy (Joules)	5	5	5
Peak Current Consumption (mA)	320	100	60
Effective Intensity (Cd)	29	29	29
Peak Intensity (Cd)	22213	22213	22213
Power Consumption (Watts)	8	11	18
NOTE: The Cd figures are for a clear lens @ 1Hz flash rate.			

FOR COLORED LENSES

Color	Red	Blue	Amber	Green	Yellow
Multiplying Factor	0.15	0.12	0.51	0.49	0.86

The photometric data has been verified by BSI.

A report is available if required.

Ordering Requirements

The following code is designed to help in the selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box. **For standard products, available ex-stock, contact sales office for details.**

Model Type	Certification	Voltage	Flash Rate	Lens Color	Lens Guard	Unit Fixing	Earth Continuity	Tag/Duty Label	Other Option	Unit Finish
XB11							N			
		Voltage	Code	Guard		Label		Option		Code
		24V d.c.	024	None		None		None		N
		110V a.c.	110	Yes		Yes		Blanking Plug		P
		240V a.c.	240			(Please specify)				
Certification		Code		Color		Continuity		Finish		Code
UL		UL		Red		None		Natural Black		N
UL (ordinary locations)		UW		Blue				Red		R
				Green				Blue		B
				Amber				Yellow		Y
				Yellow				Grey		G
				Clear				White		W
								Special Finish		S
		Flash Rate				Unit Fixing				
		60/min				Direct Mounting				
		Other flash rates available, please specify.				Backstrap				

To order ATEX approved version, see European data sheet.



All the above specifications, dimensions, weights and tolerances are nominal (typical) and MEDC reserve the right to vary all data without prior notice. No liability is accepted for any consequence of use.